

Keyless Entry and Alarm System

Model # SLI 840

The perfect alarm for any vehicle security application. Use as a keyless entry system, or a complete, multi-featured alarm.

Features:

- Miniature Alarm brain
 - All-modular connections eliminating hardwiring
 - Patented Q.O.T (Quick and Quiet Test) ensures alarm is working properly
 - Patented Fail-Safe arming verifies the alarm will arm.
 - Phase II Protection.
- Two 4-Button, 2-Channel "Icon" Remotes
 - Easy to read icons make understanding the alarm simple.
 - Up to 200 feet range. 68 billion possible codes.
 - Code learning makes it easy to add new remotes. Learn up to 4 remotes. RF CodeWash automatically deletes lost or stolen remotes every time a new remote is programmed.
 - Separate arm, disarm, and panic buttons.
 - Aux. button (*) controls chirp delete, sensor bypass, and channel 2.
- 124 dB Multi-Tone Siren and Separate Horn-honk outputs
 - Small, 3-tone, 124dB, no "toy" sounds.
 - Separate (-) horn-honk output for simultaneous use.
- Dual-Stage Shock Sensor (Patented)
 - Separate pre-intrusion & trigger adjustments.
- 7-Function LED
 - LED indicates arming status, armed, disarmed, valet mode, triggered zone
 - ID, triggered zone recall, & RF transmitter reception.
- Multi-Function Push Button
 - Activates/Deactivates valet mode.
 - For emergency disarming, code learning, & programming.
- Door Lock Outputs (+/- reversing)
 - Ignition controlled door locking & unlocking (separate).
 - Driver priority door unlock output.
 - Double pulse unlock.
- Starter Disable (- output)
 - Normally Open/Normally Closed circuit programmable.
 - Automatic Starter Disable (ASD) feature disables starter after 10 minutes for customers who want extra protection in active arming mode.
- Domelight Supervision (- output)
 - Turns vehicle's interior lights on for 30 seconds.
 - Flashes interior lights when triggered.
- 13 Programming Functions
 - Passive/active arming, chirp/nochirp, SecureLock on/off, ignition-controlled door locks on/off, steady or pulsed (horn) output on siren wire, door error chirps on/off, True trigger on/off, ASD on/off, 0.7/3.5 sec. door lock timing, double pulse unlock on/off, passenger unlock/pulsed horn output, N.O. or N.C. starter disable output.



Included:

- Two 4-button "icon" remotes, patented dual-stage shock sensor, multi-tone siren, 7-function LED, multi-function push button valet switch, pre-wired starter disable socket.

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

PI_SLI840_150811.docx