

4-Port Passive Video Transceiver

EB-P104-01Q Range: Up to 1,950ft (600m)

The ENFORCER EB-P104-01Q Passive 4-Port Video Transceiver allows CCTV cameras to connect to a DVR, video switcher, or multiplexer via inexpensive Cat5e/6 unshielded twisted pair (UTP) cable. This transceiver is a great way to cut the cost and complexity of security networks by eliminating the need to run expensive coaxial cable to multiple CCTV cameras.

Features:

- Transmits up to 1,300ft (400m) color video or up to 1,950ft (600m) B/W video
- Built-in surge protection
- Passive operation No external power required
- Transmits video over Cat5e/6
- Removable terminal blocks or RJ45 connectors
- Connects to cameras, DVRs, multiplexers, and other devices


Specifications:

Model			EB-P104-01Q
Video	Number of channels		4
	Range*	B/W	1,950ft (600m)
		Color	1,300ft (400m)
	Video format		NTSC, PAL, SECAM
	Maximum input		1.1Vp-p
	Insertion loss		<2dB per pair from DC~6MHz
	Return loss		>15dB from DC~6MHz
	Frequency response		DC~6MHz
	Common mode rejection		>40dB, 15kHz~6MHz
Connections	Wire type		UTP 24~16 AWG
	Wire category		Cat2~Cat6
	UTP Connection		Silver plated
	Attenuation		DC~6MHz, 6.6dB max.
	Impedence	Coax, male BNC	75Ω@1MHz
		Terminal block	100Ω@1MHz
		RJ45	100Ω@1MHz
Other	DC Loop resistance		52Ω/1,000ft (52Ω/305m)
	Differential capacitance		19pF/ft max. (62pF/m max.)
	Power		No power required
	Operating temperature		32 ~131 F (0 ~55 C)
	Storage temperature		-4 ~158 F (-20 ~70 C)
	Humidity range		0~95 % (Non-condensing)
	Case		Galvanized steel
	Weight		7-oz (200g)
	Dimensions		3 ¹⁵ / ₁₆ "x2 ⁷ / ₈ "x ¹⁵ / ₁₆ "
			(100x72x23 mm)

^{*}Shorter range may result when used with a DVR.



Sample Application:



Also Available from SECO-LARM:



16-Port Passive Video Transceiver EB-P116-01Q

- Connects up to 16 CCTV cameras using low-cost Cat5e/6 UTP cable to a central location
- Works in conjuction with passive or active baluns

