

Elit∈ Passive Video Balun with Terminals for Power or Data Pass-Through



EB-P501-02Q

The fast, easy, and low-cost way to connect a CCTV camera to a monitor or DVR. All SECO-LARM passive video baluns transmit the video signal of a single CCTV camera over long distances via low-cost Cat5e/6 cable. The EB-P501-02Q's patented design features built-in terminals for power OR data pass-through.

Features:

- Gold-plated BNC for greater reliability and longer life
- Transmits up to 1,300ft (400m) color video, 1,950ft (600m) B&W video
- Passive operation No external power required
- Uses low-cost Cat5e/6 cable instead of costly coaxial cable
- Terminal blocks No crimping required
- High immunity from interference
- Small size $(1^{15}/_{16}"x^{7}/_{8}"x^{9}/_{16}")$ allows for mounting multiple units behind a DVR
- Sleek design incorporates ergonomic grip for easy installation
- Patented design includes built-in terminals for power OR data pass-through
- Lifetime warranty

Specifications:

Video	Range*	B/W	1,950′ (600m)
		Color	1,300′ (400m)
	Video format		PAL, NTSC, SECAM
	Maximum input		1Vp-p
	Insertion loss		<2dB per pair from DC~6MHz
	Return loss		>18dB from DC~6MHz
	Frequency response		DC~6MHz
	Common mode rejection		60dB, 15kHz~6MHz
Connections	Wire type		UTP (Unshielded Twisted Pair) 24~16 AWG
	Wire category		Cat2 min.
	UTP Connection		Gold plated
	Attenuation		DC~6MHz, 2dB max.
	Impedance	Coax, male BNC	75Ω@1MHz
		Terminal block	100Ω@1MHz
Other	DC Loop resistance		52Ω/1000′ (18Ω/100m)
	Differential capacitance		19pF/ft max. (62pF/m max.)
	Power		No power required
	Max. amperage		3A@12VDC, 1.5A@24VAC
	Operating temperature		32°~131° F (0°~55° C)
	Storage temperature		-4°~185° F (-20°~85° C)
	Humidity range		0~95% (Non-condensing)
	Case		ABS Plastic

*Shorter range may result when used with a DVR.

16842 Millikan Ave, Irvine, CA 92606


SECO-LARM



Power OR Data Pass-Through Terminals:



Sample Application – Connecting Power:





Tel: 949-261-2999 / 800-662-0800 • Fax: 949-261-7326