

3.6mm Fixed Lens Vandal-Resistant Ball-Mount Cameras (700 TVL, 960H High Resolution)

EV-2706-N3GQ

3.6mm, 24 IR LEDs, 50' Range, Gray

EV-2706-N3WQ

3.6mm, 24 IR LEDs, 50' Range, White

Features:

- 1/3" Sony Super HAD II CCD
- 700 TV Lines
- 960H High resolution
- 3.6mm Lens
- 24 IR LEDs, 50ft IR range
- 360° Triple-Axis Rotation
- Heavy-duty vandal-resistant design
- Day/Night operation: 0 Lux LEDs on, 0.06 Lux LEDs off
- Cables concealed in bracket to prevent tampering
- Rugged, weatherproof (IP65) construction
- Split-glass design to eliminate IR reflection
- Mounting brackets available in white and gray

Optional Mounting Brackets Available:

Conduit Box	Conduit Drop	Ceiling	Wall
EV-DSSGQ* EV-DSSWQ*	EV-DDSGQ* EV-DDSWQ*	EV-DCSGQ* EV-DCSWQ*	EV-DWSGQ* EV-DWSWQ*
			

*"G" in model number indicates gray; "W" in model number indicates white.



EV-2706-N3GQ



EV-2706-N3WQ

Specifications:

Model		EV-2706-N3GQ / EV-2706-N3WQ
Chip		1/3" Sony Super HAD II CCD
Resolution		700 TV Lines
Pickup elements		976x494 (NTSC) / 976x582 (PAL)
960H*		Yes
Scanning system		2:1 Interlace
Sync		Internal
Video output		1.0V p-p composite output, 75Ω
Lens		3.6mm
# of IR LEDs		24 (850nm)
IR Range		Up to 50' (15m)
Minimum illumination	LEDs off	0.06 Lux
	LEDs on	0.0 Lux
S/N Ratio		>48dB
DSS (Digital Slow Shutter)		N/A
Operating voltage		12VDC
Current draw	LEDs off	95mA
	LEDs on	270mA
IP Rating		IP65
Operating temperature		14°~122° F (-10°~50° C)
Dimensions		3 1/16" x 3 9/32" (94x80 mm)
Cable length		38" (98cm)
Weight		14-oz (400g)

*In order to take full advantage of 960H resolution, the camera must be used with a 960H DVR.