

RS-232 to RS-485 Converter

EVA-RS1


Range: 3/4 Mile (1,200 Meters)

Features:

- 9-Pin DB-9 female connector for RS-232 to 2-Wire removable terminal block for RS-485
- Two wire, differential signals, half duplex
- No external power supply required. Port powered
- Auto-switching baud rate, speed up to 115,200 baud (115.2 kbps) over a distance of 1,200 meters
- Up to 32 devices may be connected together in RS-485 multidrop operation
- No software needed. Automatic send data control
- Removable terminal block for ease of installation and troubleshooting




Sample Installation:



Specifications:

Input	RS-232, DB9
Output	RS-485, Removable terminal block
Current consumption	10mA (max)
Transmission range	3,700 ft. / 1,200 meters
Connector	32
Power	No power required, port powered
Storage temperature	-22°~158°F (-30°~70°C)
Operating temperature	14°~113°F (-10°~45°C)
Dimensions - W x H x D	2 7/8" x 1 5/16" x 5/8" (73 x 33 x 17mm)

Dimensions:



SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved.
All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.
The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® ENFORCER® CRIMEBUSTER® CBA SLI®

EVA-RS1_150602.docx