

# Security

## **High-Intensity LED Modules**

**SL-1311-MA** High Intensity 1Wx4 LED Module

#### **Features:**

- Connect to the outside of an alarm bell box for external highintensity notification
- Fully epoxied weatherproof (IP66) and vibration-resistant design for external or internal use
- Up to 100,000 hours of continuous use
- 19 Built-in programmable flash patterns
- Up to 15 units can be synchronized to flash simultaneously or alternately
- Multi-voltage input: 10~30VDC
- Non-volatile memory recalls last flash pattern used at power-up
- · Surface mounting or flush mounting

### **Sample Applications:**

- Visual indicator for security systems
- Caution and hazard lighting
- Police and security vehicles
- Fire trucks
- Construction vehicles
- Ambulances

## **Specifications:**

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

	SL-1311-MA
Housing shape	Rectangular
# of LEDs	4 High-intensity 1W LEDs
Max. current draw	560mA@12VDC 300mA@24VDC
Operating voltage	10~30VDC
Electrical protection	Reverse polarity protected
Operating life	LEDs rated at 100,000 hours (>11 years)
# of flash patterns	19 (Programmable)
Synchronization	Sync or alternate up to 15 units
IP Rating	IP 66
Operating temperature	-22°~150° F (-30°~65° C)
Weight	5-oz (142g)
Dimensions	41/2"x11/4"x13/16" (122x31x30mm)

# 19 Programmable Flash Patterns





#### **Available in 2 Different Colors:**

LED Color	Model
Blue	SL-1311-MA/ <b>B</b>
Red	SL-1311-MA/ <b>R</b>

( E ROHIS