

4-in-1 HD TVI, CVI, AHD, Analog Vandal Dome Camera

EV-Y2201-AMWAQ 2.8~12mm, 1080p, 12VDC

Features:

- 1080p Resolution
- 2.8~12mm ICR for a wide viewing angle
- 3D-NR (3D Digital Noise Reduction)
- DWDR (Digital Wide Dynamic Range)
- 24 IR LEDs for low-light situations
- Two-axis gimbal rotation
- Joystick OSD control for easy camera programming
- Supports UTC programming
- Weatherproof (IP65) construction

















3D Digital Noise Reduction:

DNR Off

DNR On







Digital Wide Dynamic Range:

DWDR Off

DWDR On







Simulated images

SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326

Website: www.seco-larm.com Email: sales@seco-larm.com

Specifications:

		T
Туре		Vandal Dome Camera
Formats		TVI (default) / CVI / AHD / Analog
CMOS		1/2.9" 2MP Sony CMOS
Resolution (HD)		1920x1080
TV Lines (analog)		1200TVL
Video output format		NTSC/PAL
OSD (On-Screen Display)		Yes
Cable OSD control		Yes
Video output		1.0Vp-p Complex video output
Megapixels		2MP
Lens		2.8~12mm ICR
Viewing angle		30°~90°
# of IR LEDs		24 (850nm)
IR Range		Up to 100ft (30m)
FPS		30FPS
F Stop		F1.4-F1.6
Minimum illumination (IR On)		0Lux
Gamma correction		0-1
S/N Ratio		50dB
Shutter control		Yes
Gain control		Yes
White balance		Auto, Day & Night
Operating voltage		12VDC
Current Draw	(IR On)	270mA
	(IR Off)	90mA
IP Rating		IP65
Operating temperature		-4°~131° F (-20°~55° C)
Dimensions		5 ³ / ₁₆ "x4 ¹ / ₂ " (132x114 mm)
Weight		1-lb, 9.3-oz (717g)

ENFORCER

