

# Illuminated RTE Plates Slim-line

SD-7103GC-PEQ Stainless steel plate
SD-7103GC-PTQ Stainless steel plate with timer

## Features:

- Square illuminated push button with caption "PUSH TO EXIT"
- Message language can be easily changed in the field to Spanish or French
- CE and UL approved switch is rubber-sealed to prevent liquid penetration
- Includes stainless-steel slimline plate Dimensions: 4<sup>1</sup>/<sub>2</sub>"x1<sup>1</sup>/<sub>2</sub>"x1<sup>15</sup>/<sub>16</sub>" (114x38x49 mm)
- Includes six colored 12-inch wire leads with easy toattach spade lugs for fast installation
- Long-life green LED 12/24 VAC/VDC (Approx. 35,000 hrs)
- Weather resistant when properly installed

## SD-7103GC-PEQ Includes:


Momentary switch, DPST, NO/NC contacts rated 5A@24VAC max.

### SD-7103GC-PTQ Includes:

- Timed output from 1~180 s
- SPDT Switch rated 3A@24VDC
- Buzzer output for audio status


# PUSH TO EXIT SD-7103GC-PEQ SD-7103GC-PTQ

# Wiring Diagram:



\*IMPORTANT: For 24VDC operation, use the included  $680\Omega$ , 0.5W resistor in line with the red wire or the black wire.

# Timer (SD-7103GC-PTQ only):



NOTE: Terminal legend can be found on back of PCB. †Relay rated 3A@24VDC

## SECO-LARM® U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: www.seco-larm.com Email: sales@seco-larm.com



Copyright © 2020 SECO-LARM U.S.A, Inc. All rights reserved.

All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners.

The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.