

CCTV

Armored Ball Turret Camera

EV-2646-NKGQ

2.8~12 mm lens, 600TVL

Features:

- The EV-2646-NKGQ Armored Ball Turret Camera is ideal for a number of monitoring solutions that require wider viewing capabilities
- 1/3" SONY Super HAD II CCD
- 600 TV lines
- Dual voltage: 12VDC/24VAC
- Digital Noise Reduction (DNR)
- Digital Slow Shutter (DSS)
- 2.8~12mm lens
- Minimum illumination of 0.000006-lux with IR LEDs on



The EV-2646-NKGQ combines IR LEDs, Digital Noise Reduction (DNR), and a Digital Slow Shutter (DSS) that digitally slows the shutter 32 times its normal speed to capture a clear picture in total darkness.






15 Minutes Before Sunrise (Normal Picture)

15 Minutes Before Sunrise with IR LEDs, DNR, DSS

Wall Mount Bracket:





Dimensions:

SECO-LARM[®] U.S.A., Inc.

16842 Millikan Avenue, Irvine, CA 92606

Phone: (949) 261-2999 | (800) 662-0800 Fax: (949) 261-7326 Website: <u>www.seco-larm.com</u> Email: <u>sales@seco-larm.com</u> Copyright 2015 © SECO-LARM U.S.A., Inc. All rights reserved. All trademarks are the property of SECO-LARM U.S.A., Inc. or their respective owners. The SECO-LARM policy is one of continual development. For that reason, SECO-LARM reserves the right to change prices and specifications without notice. SECO-LARM is not responsible for misprints.

SECO-LARM® **ENFORCER®** CRIMEBUSTER® CBA **SLI**

pi-EV-2646-NKGQ.docxdocx

Specifications:

Type Armored Ball Turret Camera CCD 1/3" SONY Super HAD II CCD Resolution 600 TV lines Pickup Elements 768x494 pixels)
Resolution600 TV linesPickup Elements768x494 pixels	
Pickup Elements 768x494 pixels	
Video Output 1.0Vp-p composite video, 75Ω	2
Video Output Format NTSC	
Lens (DC Auto Iris) 2.8~12mm	
Minimum Illumination0.000006-lux (IR LEDs on)	
Digital Slow Shutter (DSS) 32x (Auto)	
Digital Noise Reduction (DNR) Auto	
S/N Ratio 52dB (AGC Off, Weight on)	
White Balance ATW	
Shutter Control 1/60	
Gain Control Auto Gain Control (AGC)	
IP Rating IP65	
# of Infrared LEDs 42 (850nm)	
Power Source 12VDC/24VAC	
Current Draw 450mA	
Operating Temperature 14°~122° F (-10°~50° C)	
Dimensions 5 ¹ / ₂ "x4 ³ / ₈ "x5 ¹ / ₂ " (140x111x140 m	າm)
Weight 3-lb (1.4kg)	